

# Fork capacities depending on load centres

LC (mm) basing on	80x40 ISO 2A	100x35 ISO 2A	100x40 ISO 2A	100x45 ISO 2A	120x40 ISO 2A	125x45 ISO 2A	100x45 ISO 3A	100x50 ISO 3A	120x50 ISO 3A	125x45 ISO 3A	125x50 ISO 3A	130x60 ISO 3A	140x50 ISO 3A	150x50 ISO 3A	130x60 ISO 4A	150x60 ISO 4A	150x70 ISO 4A	150x75 ISO 4A
Capacity (kg) at cross-section (mm)																		
500	2,000	2,000	2,500	2,978	2,981	2,978	3,000	3,500	4,500	4,000	5,000	5,943	5,000	5,000	7,132	8,321	10,682	11,860
600	1,677	1,676	2,097	2,500	2,500	2,500	2,518	2,940	3,780	3,357	4,200	5,000	4,200	4,200	6,000	7,000	9,000	10,000
700	1,444	1,443	1,806	2,154	2,153	2,154	2,170	2,534	3,259	2,893	3,621	4,315	3,621	3,621	5,178	6,041	7,776	8,644
800	1,268	1,266	1,585	1,892	1,890	1,892	1,906	2,227	2,864	2,541	3,182	3,795	3,182	3,182	4,554	5,313	6,844	7,612
900	1,130	1,128	1,413	1,687	1,685	1,687	1,699	1,986	2,554	2,266	2,838	3,387	2,838	2,838	4,065	4,742	6,112	6,800
1,000	1,020	1,017	1,275	1,522	1,520	1,522	1,533	1,793	2,305	2,044	2,561	3,058	2,561	2,561	3,670	4,282	5,522	6,145
1,100	929	926	1,161	1,386	1,384	1,386	1,396	1,633	2,100	1,862	2,333	2,788	2,333	2,333	3,345	3,903	5,035	5,604
1,200	852	850	1,066	1,273	1,270	1,273	1,282	1,500	1,929	1,710	2,143	2,561	2,143	2,143	3,073	3,585	4,628	5,152
1,300	788	786	985	1,177	1,174	1,177	1,185	1,387	1,783	1,580	1,981	2,368	1,981	1,981	2,842	3,316	4,281	4,766
1,400	732	730	915	1,094	1,092	1,094	1,102	1,289	1,658	1,469	1,842	2,203	1,842	1,842	2,643	3,084	3,983	4,435
1,500	684	682	855	1,022	1,020	1,022	1,030	1,205	1,549	1,373	1,721	2,059	1,721	1,721	2,471	2,882	3,723	4,146
1,600	642	640	802	959	957	959	966	1,131	1,454	1,288	1,615	1,933	1,615	1,615	2,319	2,706	3,495	3,893
1,700	605	603	756	903	901	903	910	1,065	1,370	1,213	1,522	1,821	1,522	1,522	2,185	2,549	3,294	3,669
1,800	571	569	714	854	852	854	860	1,007	1,295	1,147	1,438	1,721	1,438	1,438	2,066	2,410	3,114	3,469
1,900	542	540	677	809	807	809	815	955	1,227	1,087	1,364	1,632	1,364	1,364	1,959	2,285	2,953	3,290
2,000	515	513	644	769	767	769	775	907	1,167	1,033	1,296	1,552	1,296	1,296	1,862	2,172	2,808	3,129
2,100	491	489	613	733	731	733	739	865	1,112	985	1,235	1,479	1,235	1,235	1,775	2,070	2,677	2,982
2,200	468	467	586	700	698	700	705	826	1,062	940	1,180	1,413	1,180	1,180	1,695	1,978	2,557	2,849
2,300	448	447	560	670	668	670	675	790	1,016	900	1,129	1,352	1,129	1,129	1,622	1,893	2,448	2,727
2,400	430	428	537	642	640	642	647	758	974	863	1,082	1,296	1,082	1,082	1,556	1,815	2,347	2,615
2,500	413	411	516	617	615	617	621	728	936	829	1,040	1,245	1,040	1,040	1,494	1,743	2,254	2,512

The illustrations only represent the basic principles and do not constitute a contractual entitlement. Technical information will not be updated automatically.